

# STEEL enjoy radio system eRS4

enjoy motors®: emisores - transmitters - trasmettitori - émetteurs - Sender - transmissores

STEEL1 x 1 motor



STEEL4+ x 4 motors



433.<sub>.92</sub>  
MHz  
eRS4

safe  
rolling code  
eRS4

*Español:*

**STEEL1:** Emisor portátil y ergonómico para la gestión individual de 1 motor radio eRS4 o 1 motor electromecánico conectado a 1 receptor eRS4.

También puede utilizarse como emisor general de una agrupación, reconociéndolo de forma sencilla en tantos motores como se quieran agrupar.

**STEEL4+:** Emisor portátil y ergonómico para la gestión individualizada de hasta 4 motores radio eRS4 o 4 motores electromecánicos conectados a 4 receptores eRS4.

El emisor STEEL4+ aporta la función de centralización automática, de los 4 canales individuales, por lo que es posible comandar uno a uno cada motor (simplemente seleccionando el canal indicado en cada caso) o se puede comandar de forma agrupada los 4 motores (selecciónando el canal específico para la centralización).

- Sistema Rolling Code.
- Frecuencia 433.92 MHz.

*English:*

**STEEL1:** Portable and ergonomic transmitter to manage 1 radio motor eRS4 or 1 electromechanical motor connected to any receiver eRS4.

Also it can command a single motor or be used as general emitter command in a centralization, learning it easily in many motors as you want to add in the group.

**STEEL4+:** Portable and ergonomic transmitter to manage up to 4 radio motors eRS4 or 4 electromechanical motors connected to 4 receiver eRS4.

The transmitter STEEL4 + provides the function of Auto-centralization, for the 4 individual channels, so can commands one by one each motor (simply selecting the channel indicated in each case) or can command as a group the 4 motors (selecting the specific channel for centralization).

- Rolling Code System.
- Frequency 433.92 MHz.

## Características principales - Main characteristics - Caractéristiques principales- Caratteristiche principali - Schlüsselfestigkeiten - Características principais

Product Code	STEEL1	STEEL4+
Manage up to (individually)	1 motor	4 motors
LCD display on board	no	no
Wall holder	yes	yes
Frequency	433.92 MHz - Rolling Code	
Average range	200m free field; 20 ~ 35 m indoor	
Compatibility	eRS4	
Power supply	3V CR2430 Lithium battery	
Working current	≤ 12 mA	
Operatin time	-20°C ~ +60°C	
Protection rating	IP30	
Package quantity (pcs)	1 / 10	
Dimensions (mm)	120 x 42 x 9	
Certification - Warranty		