Español:

STEEL4: Emisor portátil y ergonómico para la gestión individualizada hasta 4 motores radio eRS4 o 4 motores electromecánicos conectados a 4 receptores eRS4. Utilizando la función S: Simple

STEEL8: Emisor portátil y ergonómico para la gestión individualizada hasta 8 motores radio eRS4 o 8 motores electromecánicos conectados a 8 receptores eRS4. Utilizando la función S: Simple

STEEL16: Emisor portátil y ergonómico para la gestión individualizada hasta 16 motores radio eRS4 o 16 motores electromecánicos conectados a 16 receptores eRS4. Utilizando la función S: Simple

Además cuentan con el modo de funcionamiento "M: Múltiple", a través del cual podemos hacer agrupaciones de motores de forma intuitiva y muy sencilla:
1- Seleccionamos el canal donde queremos tener la agrupación.
2- Seleccionamos el modo "M: Múltiple".
3- Introducimos los canales a agrupar.

English:

STEEL4: Portable and ergonomic transmitter to manage up to 4 radio motors eRS4 or 4 electromechanical motors connected to 4 receiver eRS4. By using the function S: Simple

STEEL8: Portable and ergonomic transmitter to manage up to 8 radio motors eRS4 or 8 electromechanical motors connected to 8 receiver eRS4. By using the function S: Simple

STEEL16: Portable and ergonomic transmitter to manage up to 16 radio motors eRS4 or 16 electromechanical motors connected to 16 receiver eRS4. By using the function S: Simple

Also it has the "M: Multiple" mode. In this case we can manage another 4, 8 or 16 groups in an intuitive and simple way.
1 - Select the channel where we desire do the centralization.
2 - Select the "m: multiple" mode.
3 - Enter the channel number of each motor to introduce in the group.

433.92 MHz eRS4

safe rolling code eRS4

Características principales - Main characteristics - Caractéristiques principales- Caratteristiche principali - Schlüsseleigenschaften - Características principais

Product Code	STEEL4	STEEL8	STEEL16
Manage up to (individually)	4 motors	8 motors	16 motors
LCD display on board	yes	yes	yes
Wall holder	yes	yes	yes
Frequency	433.92 MHz - Rolling Code		
Average range	200m free field; 20 ~ 35 m indoor		
Compatibility	eRS4		
Power supply	3V CR2430 Lithium battery		
Working current	≤ 12 mA		
Operatin time	-20ºC ~ +60ºC		
Protection rating	IP30		
Package quantity (pcs)	1 / 10		
Dimensions (mm)	120 x 42 x 9		
Certification - Warranty	CE enjoy 6	CE enjoy 6	CE enjoy 6